

Datasheet Plastic Collimator Lens CAW060

VIAOPTIC Part No 099-099-001-012

These data concern a full plastic aspherical bi-convex lens. It is specified for use as a collimator in combination with a diode laser. It can be mounted by use of glue or spring-loaded. Mechanical lock-mounting is not advisable because of possible distortions.

Parameters	Wavelength 655 nm	Unit
Design conditions		
<i>N.A.</i>	0.22	--
Clear Aperture <i>CA</i>	2.2	mm
Designed with laser cover glass (<i>BK7</i>) on source side:		
Distance from source	0.55	mm
Glass thickness	0.25	mm
Optical parameters		
Focal Length	6.00	mm
Back Focal Length <i>BFL</i>	4.82	mm
Back Focal Length <i>BFL (with 0.25mm laserglass)</i>	4.90	mm
Free Working Distance <i>FWD</i>	4.67	mm
Free Working Distance <i>FWD (with 0.25mm laserglass)</i>	4.75	mm
<i>RMS</i> mean	on axis	30
		mλ
Optical Tolerance	0.1	mm
Mechanical parameters		
Mounting hole diameter <i>D_{mh}</i>	Ø 5.00	mm
Other parameters: see drawing		
Environmental stability		
Storage Temperature	< 90	°C
Operating Temperature	-20 to 80	°C

General Data: Transmission [%]: 90 Lens Material: COP

Specifications subject to change without notice.
Zemax catalogue file available.